

SV 104IS

Intrinsically Safe Noise Dosimeter

The SV104IS is the intrinsically safe version of the revolutionary personal noise dosimeter, the SV104. Both instruments offer a new approach to occupational health and safety noise monitoring presenting features such as 1/1 octave band real-time analysis and audio events recording functions which are a new quality in an instrument of this size. All results are clearly displayed on the amazing OLED screen which offers excellent visibility even in full daylight or darkness.


This personal dosimeter has a robust 1/2" MEMS microphone enabling easy calibration using most commonly available acoustic calibrators. The new microphone has a large dynamic range of the 90 dB which allows to measure noise from 60 dBA to 140 dBA. The long list of microphone advantages includes also the auto-calibration feature and TEDS memory that stores the calibration info in the microphone itself. The auto-calibration means performing

the acoustic calibration automatically once the microphone is inserted into the calibrator.

The SV104IS is a cable-free dosimeter and is typically attached to the user's shoulder, close to the ear using the mounting clips supplied. The instrument works with Svantek's health and safety software package, "Supervisor", that provides various tools for data analysis and reporting. The docking station supports data transfer to the PC through the infrared interface as well as handles the battery charging. Rechargeable batteries of SV104IS are able to power the instrument for 50 hours.

Features

- Intrinsic safety in accordance to ATEX and IECEx
- Personal Noise Dosimeter conforming to IEC 61252 and ANSI S1.25
- Class 2 in accordance to IEC 61672
- Measurement range 60 dBA RMS ÷ 140 dBA Peak
- Automatic calibration start (auto-calibration)
- Vibration shock detection and recording
- Three parallel measurement profiles
- $L_{(C-A)}$ calculation
- 1/1 octave real-time analysis (option)
- Voice comments recording before and after measurement
- Audio events recording during measurement (option)
- OLED color display with super brightness and contrast
- Easy in use predefined setups
- Operational time > 50 hours



SV 104IS

Technical Specification

Noise Dosimeter

Standards	IEC 61252 ed1.1 (2002); ANSI S1.25-1991 (R2007); Class 2 IEC 61672-1 ed2.0 (2013) ATEX: EN 50303:2000, EN 60079-0:2012, EN 60079-11:2012, EN 60079-26:2007; certificate number: FTZU 14 ATEX 0055X IEC 60079-0 ed6.0 (2011), IEC 60079-11 ed6.0 (2011), IEC 60079-26 ed2 (2006); certificate number IECEx FTZU 15.0001X
Weighting filters	A, C and Z
Time constants	Slow, Fast, Impulse
Exchange rates	2, 3, 4, 5, 6
Measurement results	Run Time (TIME), L_{peak} , L_{max} , L_{min} , L, DOSE (%), Projected Dose D_{8h} , Projected Dose PrDOSE, Leq, LAV, LE, SEL8, E, E_{8h} , LEPd, PSEL, Ltm3, Ltm5, Ln statistics, Peak Threshold Counter (PTC), PTP, Upper Limit Time (ULT), TWA, Projected TWA (PrTWA), Lc-a, OVL
Measurement Profiles	3
Microphone	Class 2 microphone, 1/2" housing
Measurement Range	60 dBA RMS ÷ 140.1 dBA Peak
Frequency Range	20 Hz ÷ 10 kHz
Dynamic Range	90 dB
Data Logging ¹	Summary results for the measurement time and Time-history logging of Leq/Max/Min/Peak with adjustable logger step
Audio Recording	Audio events recording on trigger (option)
Voice Comments	Audio records on demand, created before or after measurement, added to measurement file
1/1 Octave ¹	Single channel 1/1 octave real-time analysis and spectra logging, 9 filters with centre frequencies from 31.5 Hz to 8 kHz (option)

Basic Data

Display	OLED 128 x 64 pixels
Ingress protection	IP 65
Memory	64 MB
Interface	Infrared(docking station necessary)
Keyboard	3 push buttons
Power Supply	Rechargeable cell operation time > 50 hours ²
Environmental Conditions	Temperature from -10 °C to 50 °C Humidity up to 90 % RH, non-condensed

Dimensions	88 x 49.5 x 19.2 mm
Weight	117 grams with battery

¹function parallel to the acoustic dosimeter mode
²depends on configuration and environmental conditions



Continuous product development and innovation are the policy of our company. Therefore, we reserve the right to change the specifications without prior notice.

SVANTEK Sp. z o. o.
ul. Strzygłowska 81, 04-872 WARSAW, POLAND
phone/fax (+48) 22 51 88 320, (+48) 22 51 88 312
<http://www.svantek.com> e-mail: office@svantek.com.pl



Environmental Analytical Systems
286 Mask Island Dr.
Barry's Bay ON K0J 1B0
Tel: 613 756 0101
Toll free: 800 427 8591
E-Mail: info@enviro-analytical.com